



**BELT TECH
INDUSTRIAL**

perma

perma lubrication systems

Applications and Use



**Conveyors
& Pumps**

**Electric
Motors**

**Blower
& Fans**



Contact Us

sales@belttech1.com

www.belttech1.com



or Call Toll Free

877-554-BELT



Product	Lubricants	Discharge period	Mode	Max. lube-points	Max. pressure [bar/psi]	Operating temperature [°F]	Operating temperature [°C]	Volume [cc]	Drive / Power supply	Activation / Setting	Machine elements							Certifications	
Single-point lubrication systems, electrochemical																			
	CLASSIC / FUTURA	Grease up to NLGI 2 / Oil	1, 3, 6, 12 months (1)	Time	1	4 / 58	32 to 104	0 to +40	120	Electro-chemical	Activator screw								
	FLEX		1, 2, 3, ... , 12 months (1)			5 / 73	-4 to 140	-20 to +60	60 / 125	Electro-chemical / Integrated battery	Dial / Rotary switch								
	NOVA		1, 2, 3, ... , 12 months (2)			6 / 87	-4 to 140	-20 to +60	65 / 125	Gas generating cell / Integrated battery	Push button control and display								
Single-point lubrication systems, electromechanical																			
	STAR VARIO	Grease up to NLGI 2 / Oil	1, 2, 3, ... , 12 months	Time	1	6 / 87	-4 to 140	-20 to +60	60, 120, 250	Drive motor / Battery	Push button control and display								
	STAR CONTROL		Customized	Time / Impulse			-4 to 140	-20 to +60		Drive motor / 9-30 V DC									
Multi-point lubrication systems, electromechanical																			
	PRO MP-6	Grease up to NLGI 2	1 day to 24 months	Time / Amount	6	25 / 360	-4 to 140	-20 to +60	250, 500	Drive motor / Pump / Battery	Display with menu navigation							-	

(1) depending on ambient temperature and counter-pressure
(2) depending on counter pressure

All perma products are approved according to CE directives



877-554-BELT (2358)



sales@belttech1.com



www.belttech1.com